


SPAX®



SPAX – Construction

SPAX
For wood construction.

MADE IN
Germany

Content

Information



Certified proof of origin	4–5
Information about the CE marking and technical monitoring	6–9
Partner of Holzbau Deutschland (Association of German Carpenters)	10–11
SPAX Product characteristics and BIT-programme	12–17
Brief overview of the product range	18–19

WIROX

WIROX®

CHROME(VI)
FREE

A9J



Technical information	20–21
Full thread with flat countersunk head Outer diameter Ø 8/10/12 mm	 22–23
Partial thread with flat countersunk head Outer diameter Ø 8/10/12 mm	 24–27
Partial thread with washer head Outer diameter Ø 6/8/10 mm	 28–31
Full thread with cylindric head Outer diameter Ø 6/8 mm	 32–33
Fixing thread with cylindric head Outer diameter Ø 10 mm	 34–35
SPAX Design guidelines	36–41

Blue zinc plated

A2J

SPAX threaded rod

Full thread without head or with hex head

Outer diameter Ø 16 mm



42–44

Wood construction accessories

SPAX Screwing aid and SPAX-screw-sleeve

45



42

Stainless steel



A2
AISI 304

A4
AISI 316

Technical information

46–47

Full thread with flat countersunk head

Outer diameter Ø 10 / 12 mm



48–49

Partial thread with flat countersunk head

Outer diameter Ø 8 mm



48–49

Partial thread with washer head

Outer diameter Ø 8 mm



50–51



46

Service

SPAX Design Software

52–53

SPAX Downloadportal

54–55



52



SPAX – guaranteeing quality and innovation since 1823.

Guaranteed by us, certified by TÜV –
SPAX, located in Germany.

Certified proof of origin

for product clarity and consumer protection.

Our SPAX branded products can be purchased around the globe, in the familiar green packaging that specifies their origin in the address field: **Ennepetal – company head office and production location.** And this is exactly where the certification “Made in Germany” was carried out for SPAX screws by the German Technical Inspection Agency (TÜV) during a sophisticated test procedure.

SPAX International is and will remain based in Germany. This, in particular, guarantees its customers the high degree of safety, quality and continuity associated with the name SPAX.

SPAX – Made in Germany

Impressive advantages:

- With certified proof of origin
- Company head office and production location Germany
- Offers a high degree of safety, quality and continuity for the customer



MADE IN
Germany



SPAX video
“TÜV certification”



**CE marking and declaration
of performance (DoP) –
Quality made in Germany**

CE marking and declaration of performance (DoP) in accordance with the EU Construction Products Regulation

The commitment of SPAX International

The new Construction Products Regulation (CPR) No. 305/2011, which replaces the previous Construction Products Directive (CPD) 89/106/EEC, has been in effect since 1 July 2013.

Issuing a declaration of performance (DoP) is a fundamental change for manufacturers of construction projects.

Products will continue to be labelled with the CE marking, but the marking now also includes the number of the declaration of performance.

SPAX International provides the utmost transparency for its customers by including all items in the declaration of performance. The European Technical Assessment ETA-12/0114 dated 10 July 2017 (modified as of 12 Oct. 2017) is now the applicable basis for the assessment and CE marking of our products in accordance with the EU Construction Products Regulation (Regulation (EU) No. 305/2011).

In this way, the declaration of performance is unambiguously associated with the product and vice versa.



- 1 European Technical Approval ETA
- 2 Declaration of Performance (DoP)
- 3 CE marking



downloads.spax.com



SPAX – Voluntary technical monitoring.


Safety
is the point.

Voluntary technical monitoring for your safety

A resolution of the EU Commission moderated the system for the assessment and verification of constancy of performance (AVCP system), which also applies for SPAX products, and downgraded the requirement level from 2+ to 3. This affects all of the SPAX products governed by European Technical Approval ETA and, therefore, labelled with a CE marking. Level 3 means that external monitoring by an independent materials testing institute as a recognised certification body is no longer required. For this reason, only in-house production control is necessary in the future.

From the SPAX perspective, this downgrade in level represents a departure from the proven principle of dual control, which can result in a loss of trust by users in the long run. In the end, customers can no longer trust the products in the same way as before.

To counteract these circumstances, **SPAX is subjecting its products to voluntary technical monitoring by the Materials Testing Institute at the University of Stuttgart (MPA Stuttgart).** Therefore, our products will be clearly labelled with the MPA Stuttgart testing seal on the product packaging. This means that our SPAX products will continue to be tested and inspected externally on an ongoing basis.



1 Certificate

2 MPA logo

For this reason, our customers can continue to place their full and complete trust in SPAX quality, which is tested by an independent body. Because it's safety first at SPAX! This is why we do our best at SPAX to guarantee the safety of our products and, hence, our customers' safety.

Expiration of the general construction approvals for SPAX since 1 Aug. 2017

The general construction approvals (Allgemeine bauaufsichtliche Zulassungen (abZ)) for SPAX screws have been expired since 1 Aug. 2017 and will no longer be renewed. After the expiration date of the abZ, only the European Technical Assessments (ETA) can be consulted, which result in products labelled with the CE marking.



downloads.spax.com



SPAX – Strong partnership

Holzbau Deutschland –
An influential partner.



© Swantje Küttner

SPAX is a strong partner

Working together to create a larger market for wood construction

The partners of Holzbau Deutschland (Association of German Carpenters) consist of a group of manufacturers of construction materials, elements and machinery together with Holzbau Deutschland in the Zentralverband des Deutschen Baugewerbes (central association of the German construction industry) and its state associations. The common goal is to support carpentry and wood construction businesses with coordinated, effective measures in marketing and education. It's about creating a larger market for the German wood construction industry. The partnership was initiated in 2000. Now there are more than 20 partners in the group.

The following projects, among others, are being implemented together:

■ Support for the German National Carpentry Team

There are no better ambassadors for the wood construction industry than the ambitious and successful German national team. Since 2008, the partners of Holzbau Deutschland have supported the extremely successful team made up of the best, up and coming talent in the field of carpentry. At the 2015 World Championships, the team won the gold medal, and in 2016 they were European champions in the individual and team classifications for the third time in a row. The German national team is a significant and popular symbol for the entire profession and provides considerable support for recruiting the next generation of carpenters.

■ The "HOLZ KANN!" information portal

The goal of the "Holz kann!" ("Do it with wood") campaign website is to help builder-owners and clients understand the advantages of wood in construction and renovation. The website primarily addressed builder-owners in the private sector and presents construction with wood in a neutral, comprehensive and competent manner. In this way, the partners hope to strengthen the demand for wood construction and demonstrate everything wood can do: a lot!

■ German Wood Construction Award

The Deutsche Holzbaupreis (German Wood Construction Award) honours buildings and building components consisting mainly of wood and wood materials as well as other renewable raw materials and which demonstrate the spectrum of applications for wood in an exemplary manner. The German Wood Construction Award has been presented biannually since 2003 and is now considered the most important award for building with wood in Germany. The partners supported this prize for the first time in 2017.

■ University Award for Wood Construction

The Hochschulpreis Holzbau (University Award for Wood Construction) honours students in architecture and construction engineering in order to support exemplary and creative work with wood materials in construction and development. Prizes are awarded for designs of buildings consisting mainly of wood and wood materials as well as other renewable raw materials. The award is given in connection with the prestigious Deutscher Holzbaupreis (German Wood Construction Award). The University Award for Wood Construction for 2017 was presented in May 2017 at the LIGNA trade fair in Hannover.

■ Zimmermeister-Suche.de

The Zimmermeister-Suche.de website is the largest search machine for carpentry businesses in Germany. All industry enterprises in Holzbau Deutschland (Association of German Carpenters) are automatically listed here, at no cost, of course. A geo-data search displays the location of the business for users. Businesses can add the services they provide and a link to their own websites.

■ Education projects

Together with its partners, Holzbau Deutschland (Association of German Carpenters) carries out various education projects. Information about technical development and standards as well as workplace safety in wood construction is provided to master training institutes and education facilities.

© Swantje Küttner



SPAX – Construction

A new surface –
for weatherproof outdoor applications too.




The surface with **high corrosion protection.**

The new SPAX finish offers greater corrosion protection than bright zinc plating and has a considerably higher surface hardness. This makes it ideal for use in outdoor applications in structures such as carports or pergolas without direct exposure to weather. It also provides a significantly greater surface hardness than conventional yellow zinc plating or zinc flake coating, so it has better resistance properties in response to mechanical stress.

The advantages and properties at a glance:

- Is particularly suited to service class 2 in accordance with Eurocode 5 for open constructions without direct exposure to weather, such as car ports or pergolas
- Trotz der hohen Korrosionsbeständigkeit von WIROX® kann damit **Edelstahl rostfrei nicht ersetzt** werden.
- Is mechanically resistant
- Is free of chrome(VI) and far more **environmentally-friendly** than conventional surfaces, both during manufacturing and usage



SPAX video
"Salt spray test"


Product characteristics

SPAX technology and application: **Thread and point**



4CUT at the thread

Starting at screw lengths of 160 mm, the special moulding at the thread of partial thread screws significantly reduces the screwing-in torque.



4CUT in the screw point and Ground serrations

4CUT: No pre-drilling (wood-dependent), its point effectively reduces the splitting effect. The square end pushes aside the fibre of the wood and reduces the screwing-in torque.

Ground serrations: For a quick and secure fastening.

Your advantage: Lower minimum clearances and lower minimum wood thicknesses in accordance with ETA.



CUT point and SPAX typical ground serrations

CUT-point: Precision placement allows screwing in without pre-drilling (wood-dependent). Effectively reduces splitting of the wood.


SPAX typical ground serrations: For a quick and secure fastening.

Your advantage: Lower minimum clearances and lower minimum wood thicknesses in accordance with ETA.

SPAX technology and application: **Various head shapes**

MULTI Head

Flush countersinking. Mills in wood and stops on metal. Length and manufacturer marking on the head.



Flat countersunk head T-STAR plus with milled ribs

Flush countersinking. Countersinks the screw head flush into the wood.



Washer head

Better tightening of connections also of warped boards. Easy bolting of steel parts and sheet metal to wood without prior counter boring of the bore hole. Guarantees higher beam supporting forces and allows savings with regard to piece numbers and working time.

Particularly suited for rafter connections.



Cylindric head


Low splitting effect when sinking the head. Can be easily countersunk in wood.

Barely visible due to small head diameter.



Product characteristics

T-STAR *plus* – The innovative recess



T-STAR *plus*

The SPAX T-STAR *plus* recess offers all the advantages of the T-STAR recess (no cam-out effect, minimises contact pressure force, accepts higher torques). In addition, this recess has a small depression in the screw head below the driving surface, into which the appropriate T-STAR *plus* BIT with guide cone can be inserted precisely. This T-STAR *plus* connection ensures optimal force transmission, a long service life for the T-STAR *plus* BITS, and a perfect fit. SPAX can even be used overhead because the screw is easier to guide and can no longer fall off the BIT.

T-STAR *plus* – Positive and secure fit of the BIT and better driving




SPAX-BIT-program

SPAX-BITs are specifically designed for hand held screw drivers, electric mains powered and battery screw drivers and even industrial pneumatic machines. SPAX-BITs give perfect fit as well as optimum hardness to ensure long life.

The SPAX BITcheck T-STAR *plus* offers a simple colour coding system, which makes it easy to find the right size at the right time. A glance and a grab and you're set.

The SPAX BITcheck T-STAR *plus* is a practical accessory and is offered together with the Rapidaptor bit receiver (50 mm).

Application note: Do not use SPAX bits in lengths of 50 mm and 35 mm in the bit receiver; instead, these must be inserted directly into the chuck of the cordless screwdriver or drill.



SPAX-BIT-program

T-STAR plus – Programme overview

SPAX-BITs T-STAR plus	Holding fixture 1/4" hexagon					
25 mm length						
Blade size	T 10	T 15	T 20	T 25	T 30	T 40
	3.0	3.5	3.5 4.0 4.5 5.0	Decking 5.0 for A2 6.0 for A4	6.0	8.0
SPAX-No.	5000009182109	5000009182159	5000009182209	5000009182259	5000009182309	5000009182409
EAN-No.	4003530239632	4003530239649	4003530239656	4003530239663	4003530239670	4003530239687



SPAX-BITs T-STAR plus	Holding fixture 1/4" hexagon					
50 mm length						
Blade size	T 10	T 15	T 20	T 25	T 30	T 40
For SPAX thread Ø [mm]	3.0	3.5	3.5 4.0 4.5 5.0	Decking 5.0 for A2 6.0 for A4	6.0	8.0
SPAX-No.	5000009183109	5000009183159	5000009183209	5000009183259	5000009183309	5000009183409
EAN-No.	4003530192852	4003530192869	4003530192876	4003530192883	4003530192890	4003530192906



SPAX-BITs T-STAR plus	Holding fixture 1/4" hexagon	
35 mm length		
Blade size	T 50	
For SPAX thread Ø [mm]	10.0 / 12.0	
SPAX-No.	5077701516035	
EAN-No.	4003530241918	



Brief overview



Flat countersunk head T-STAR <i>plus</i>									
WIROX® CHROME(VI) FREE A9J					1.4567		1.4578		
Length [mm]	8.0		10.0		Ø d ₁ , [mm] 12.0		8.0	10.0	12.0
	15.1		18.6		Ø d _k , [mm] 22.6 18.6		15.1	18.6	18.6
80	□		□				□		
100	□		□		□		□		
120	□	■	□	■			□		
140	□	■	□				□		
160	□	■	□	■	□		□	■	
180	□	■	□		□		□		
200	□	■	□	■		■	□	■	
220	□	■	□	■	□		□		
240	□	■	□	■	□	■	□	■	
260	□	■	□	■			□	■	
280	□	■	□	■		■	□	■	
300	□	■	□	■		■	□	■	
320	□		□						
340	□		□						
350		■		■	□	■		■	
360	□		□						
380	□		□						
400	□	■	□	■		■		■	■
450	□	■	□	■	□	■			■
500		■		■	□	■			■
550		■		■	□	■			■
600		■		■	□	■			
700				■					
800				■					

■ T-STAR *plus*, Full thread
 □ T-STAR *plus*, Partial thread

Washer head T-STAR plus

WIROX® CHROME(VI) FREE A9J			Rost frei A2 1.4567 304		
Length [mm]	6.0	8.0	10.0	6.0	8.0
	13.6	20.0	25.0	13.6	20.0
40	■				
50		■*			■
60	■			■	■
80	■	■	■	■	■
100	□	■	■	□	■
120	□	■	■	□	■
140	□	□	□	□	□
160	□	□	□		□
180	□	□	□		□
200	□	□	□		□
220	□	□	□		□
240		□	□		□
250	□	□	□		
260		□	□		□
280	□	□	□		□
300	□	□	□		□
320		□	□		
340		□	□		
360		□	□		
380		□	□		
400		□	□		
450		□	□		
500		□			
550		□			



Cylindric head T-STAR plus

WIROX® CHROME(VI) FREE A9J		
Ø d _i , [mm] 6.0		
Ø d _k , [mm] 8.4		
Length [mm]	80	■
	100	■
	120	■
	140	■
	160	■
	180	■
	200	■



Cylindric head T-STAR plus

WIROX® CHROME(VI) FREE A9J				
Ø d _i , [mm] 8.0				
Ø d _k , [mm] 10.0				
Length [mm]	160	■	300	■
	180	■	350	■
	200	■	400	■
	220	■	450	■
	240	■	500	■
	260	■	550	■
	280	■	600	■





SPAX – Construction

The wood construction range
with new surface



Bürgerhaus Altdorf
© Volker Winkler

Our wood construction range

Our new finish protects the environment. It does not contain chrome(VI), so it is considerably more environmentally conscious than conventional surfaces in terms of both manufacturing and use. Both users and the environment benefit from this innovation. **Trotz der hohen Korrosionsbeständigkeit von WIROX® kann damit Edelstahl rostfrei nicht ersetzt werden.**



Technical directive

RoHS – EC Directive 2002/95/EC
“Restriction of the use of certain hazardous substances”




Complies with RoHS

REACH – Regulation (EC)
No. 1907/2006 “Registration, Evaluation, Authorisation and Restriction of Chemicals”

Complies with REACH



SPAX screw finder




Flat countersunk head, Full thread, T-STAR plus

MULTI Head, CUT point, case hardened, slide-coated


A9J



Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length full thread LgV	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
8.0 Ø dk = 15.1 mm	120		40	50	500	14,000	1201010801205	4003530257278
	140		40	50	500	14,000	1201010801405	4003530257285
	160		40	50	500	14,000	1201010801605	4003530245992
	180		40	50	500	14,000	1201010801805	4003530246005
	200		40	50	500	12,000	1201010802005	4003530246012
	220		40	50	500	12,000	1201010802205	4003530246029
	240		40	50	–	4,800	1201010802405	4003530246036
	260		40	50	–	4,800	1201010802605	4003530246043
	280		40	50	–	4,800	1201010802805	4003530246050
	300		40	50	–	4,800	1201010803005	4003530246067
	350		40	50	–	3,600	1201010803505	4003530246074
	400		40	50	–	3,600	1201010804005	4003530246081
	450		40	50	–	3,000	1201010804505	4003530246098
	500		40	25	–	1,200	1201010805005	4003530246104
	550		40	25	–	1,200	1201010805505	4003530246111
	600		40	25	–	1,200	1201010806005	4003530246128
10.0 Ø dk = 18.6 mm	120		50	50	500	12,000	1201011001205	4003530257469
	160		50	50	500	14,000	1201011001605	4003530252273
	200		50	50	500	12,000	1201011002005	4003530246135
	220		50	50	500	12,000	1201011002205	4003530246142
	240		50	50	–	4,800	1201011002405	4003530246159
	260	Thread	50	50	–	4,800	1201011002605	4003530246166
	280	close	50	50	–	4,800	1201011002805	4003530246173
	300	to	50	50	–	4,800	1201011003005	4003530246180
	350	head	50	50	–	3,600	1201011003505	4003530246197
	400		50	50	–	3,600	1201011004005	4003530246203
	450		50	50	–	3,000	1201011004505	4003530246210
	500		50	25	–	1,200	1201011005005	4003530246227
	550		50	25	–	1,200	1201011005505	4003530246234
	600		50	25	–	1,200	1201011006005	4003530246241
	700		50	25	–	800	1201011007005	4003530257476
	800		50	25	–	800	1201011008005	4003530246258
12.0 Ø dk = 18.6 mm	200		50	25	250	6,000	1201011202005	4003530246265
	240		50	25	–	2,400	1201011202405	4003530246272
	280		50	25	–	2,400	1201011202805	4003530246289
	300		50	25	–	2,400	1201011203005	4003530246296
	350		50	25	–	1,800	1201011203505	4003530246302
	400		50	25	–	1,800	1201011204005	4003530246319
	450		50	25	–	1,500	1201011204505	4003530246326
	500		50	25	–	1,500	1201011205005	4003530246333
	550		50	20	–	960	1201011205505	4003530246340
	600		50	20	–	960	1201011206005	4003530246357



Shear




Withdrawal

Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product			Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]			Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length full thread LgV	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	f _{ax,d1,k} [N/mm]	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	f _{ax,d1,k} [N/mm]
8.0 $\varnothing$ d _k = 15.1 mm	120		60	60	3,995	60	60		10	120	6,253	10	120	
	140		70	70	4,235	70	70		10	130	6,733	10	130	
	160		80	80	4,475	80	80		10	150	7,213	10	150	
	180		90	90	4,715	90	90		10	170	7,227	10	170	
	200		100	100	4,955	100	100		10	190	7,227	10	190	
	220		110	110	5,110	110	110		10	210	7,227	10	210	
	240		120	120	5,110	120	120	96,0	10	230	7,227	10	230	96,0
	260		130	130	5,110	130	130	N/mm	10	250	7,227	10	250	N/mm
	280		140	140	5,110	140	140		10	270	7,227	10	270	
	300		150	150	5,110	150	150	Max,	10	290	7,227	10	290	Max,
	350		175	175	5,110	175	175	f _{ax,d1,k}	10	340	7,227	10	340	f _{ax,d1,k}
	400		200	200	5,110	200	200	=13,1kN	10	390	7,227	10	390	=13,1kN
	450		225	225	5,110	225	225		10	440	7,227	10	440	
	500		250	250	5,110	250	250		10	490	7,227	10	490	
	550		275	275	5,110	275	275		10	540	7,227	10	540	
	600		300	300	5,110	300	300		10	590	7,227	10	590	
10.0 $\varnothing$ d _k = 18.6 mm	120		60	60	5,300	60	60		10	120	8,384	10	110	
	160		80	80	5,992	80	80		10	150	9,534	10	150	
	200		100	100	6,567	100	100		10	190	10,443	10	190	
	220		110	110	6,855	110	110		10	210	10,443	10	210	
	240		120	120	7,142	120	120		10	230	10,443	10	230	
	260	Thread	130	130	7,384	130	130	115,0	10	250	10,443	10	250	115,0
	280	close	140	140	7,384	140	140	N/mm	10	270	10,443	10	270	N/mm
	300	to	150	150	7,384	150	150		10	290	10,443	10	290	
	350	head	175	175	7,384	175	175	Max,	10	340	10,443	10	340	Max,
	400		200	200	7,384	200	200	f _{ax,d1,k}	10	390	10,443	10	390	f _{ax,d1,k}
	450		225	225	7,384	225	225	=21,5kN	10	440	10,443	10	440	=21,5kN
	500		250	250	7,384	250	250		10	490	10,443	10	490	
	550		275	275	7,384	275	275		10	540	10,443	10	540	
	600		300	300	7,384	300	300		10	590	10,443	10	590	
	700		350	350	7,384	350	350		10	690	10,443	10	690	
	800		400	400	7,384	400	400		10	790	10,443	10	790	
12.0 $\varnothing$ d _k = 18.6 mm	200		100	100	8,288	100	100		12	188	13,258	10	190	
	240		120	120	8,948	120	120		12	228	14,108	10	230	
	280		140	140	9,608	140	140	132,0	12	268	14,108	12	268	132,0
	300		150	150	9,938	150	150	N/mm	12	288	14,108	12	288	N/mm
	350		175	175	9,976	175	175		12	338	14,108	12	338	
	400		200	200	9,976	200	200	Max,	12	388	14,108	12	388	Max,
	450		225	225	9,976	225	225	f _{ax,d1,k}	12	438	14,108	12	438	f _{ax,d1,k}
	500		250	250	9,976	250	250	=29,2kN	12	488	14,108	12	488	=29,2kN
	550		275	275	9,976	275	275		12	538	14,108	12	538	
	600		300	300	9,976	300	300		12	588	14,108	12	588	


Multiply the value $f_{ax,d1,k}$ with the effective thread length (l_{ef}) in the respective wood component. Lower as appropriate for angle $\alpha < 90^\circ$.
The design value for thread load-carrying capacity must not exceed the design value for steel load-carrying capacity $f_{tens,d}$.

For more information regarding measurement and design, see the SPAX design information at <https://downloads.spax.com>



Flat countersunk head, Partial thread, T-STAR plus


4CUT, MULTI Head, case hardened, slide-coated




A9J



Dimensions [mm]				Packaging units			SPAX-No,	EAN code
Thread Ø d1	Length total Ls	Length partial thread LgT	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
8.0 Ø d _k = 15.1 mm	80	47	40	50	500	14,000	0191010800805	4003530243837
	100	57	40	50	500	14,000	0191010801005	4003530244100
	120	70	40	50	500	14,000	0191010801205	4003530244117
	140	80	40	50	500	14,000	0191010801405	4003530244124
	160	80	40	50	500	14,000	0191010801605	4003530244131
	180	80	40	50	500	14,000	0191010801805	4003530244148
	200	80	40	50	500	12,000	0191010802005	4003530244155
	220	80	40	50	500	12,000	0191010802205	4003530244162
	240	80	40	50	–	4,800	0191010802405	4003530244179
	260	80	40	50	–	4,800	0191010802605	4003530244186
	280	80	40	50	–	4,800	0191010802805	4003530244193
	300	80	40	50	–	4,800	0191010803005	4003530244209
	320	80	40	50	–	3,600	0191010803205	4003530244216
	340	80	40	50	–	3,600	0191010803405	4003530244223
	360	80	40	50	–	3,600	0191010803605	4003530244230
	380	80	40	50	–	3,600	0191010803805	4003530244247
	400	80	40	50	–	3,600	0191010804005	4003530244254
	450	80	40	50	–	3,000	0191010804505	4003530244261
10.0 Ø d _k = 18.6 mm	80	50	50	50	500	14,000	0191011000805	4003530244278
	100	60	50	50	500	14,000	0191011001005	4003530244285
	120	80	50	50	500	14,000	0191011001205	4003530244292
	140	80	50	50	500	14,000	0191011001405	4003530244308
	160	80	50	50	500	14,000	0191011001605	4003530244315
	180	80	50	50	500	14,000	0191011001805	4003530244322
	200	80	50	50	500	12,000	0191011002005	4003530244339
	220	80	50	50	500	12,000	0191011002205	4003530244346
	240	80	50	50	–	4,800	0191011002405	4003530244353
	260	80	50	50	–	4,800	0191011002605	4003530244360
	280	80	50	50	–	4,800	0191011002805	4003530245329
	300	80	50	50	–	4,800	0191011003005	4003530245336
	320	80	50	50	–	3,600	0191011003205	4003530245343
	340	80	50	50	–	3,600	0191011003405	4003530245350
	360	80	50	50	–	3,600	0191011003605	4003530245367
	380	80	50	50	–	3,600	0191011003805	4003530245374
	400	80	50	50	–	3,600	0191011004005	4003530245381
	450	80	50	50	–	3,000	0191011004505	4003530245398



Shear




Withdrawal

Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal


Product			Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]			Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length partial thread LgT	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]
8.0 $\varnothing d_k = 15.1 \text{ mm}$	80	47	30	50	2,600	30	47	2,713	10	70	4,738	10	47	4,512
	100	57	40	60	2,889	40	57	2,713	10	90	4,981	10	57	5,472
	120	70	50	70	3,436	50	70	3,527	10	110	5,293	10	70	6,720
	140	80	60	80	3,436	60	80	3,527	10	130	5,533	10	80	7,680
	160	80	80	80	3,436	80	80	3,527	10	150	5,533	10	80	7,680
	180	80	100	80	3,436	100	80	3,527	10	170	5,533	10	80	7,680
	200	80	120	80	3,436	120	80	3,527	10	190	5,533	10	80	7,680
	220	80	140	80	3,436	140	80	3,527	10	210	5,533	10	80	7,680
	240	80	160	80	3,436	160	80	3,527	10	230	5,533	10	80	7,680
	260	80	180	80	3,436	180	80	3,527	10	250	5,533	10	80	7,680
	280	80	200	80	3,436	200	80	3,527	10	270	5,533	10	80	7,680
	300	80	220	80	3,436	220	80	3,527	10	290	5,533	10	80	7,680
	320	80	240	80	3,436	240	80	3,527	10	310	5,533	10	80	7,680
	340	80	260	80	3,436	260	80	3,527	10	330	5,533	10	80	7,680
	360	80	280	80	3,436	280	80	3,527	10	350	5,533	10	80	7,680
	380	80	300	80	3,436	300	80	3,527	10	370	5,533	10	80	7,680
	400	80	320	80	3,436	320	80	3,527	10	390	5,533	10	80	7,680
	450	80	370	80	3,436	370	80	3,527	10	440	5,533	10	80	7,680
10.0 $\varnothing d_k = 18.6 \text{ mm}$	80	50	40	40	3,293	30	50	3,626	10	70	6,312	10	50	5,750
	100	60	40	60	3,770	40	60	3,626	10	90	6,946	10	60	6,900
	120	80	50	70	4,131	40	80	3,626	10	110	7,521	10	80	9,200
	140	80	60	80	4,796	60	80	4,714	10	130	7,521	10	80	9,200
	160	80	80	80	4,870	80	80	4,714	10	150	7,521	10	80	9,200
	180	80	100	80	4,870	100	80	4,714	10	170	7,521	10	80	9,200
	200	80	120	80	4,870	120	80	4,714	10	190	7,521	10	80	9,200
	220	80	140	80	4,870	140	80	4,714	10	210	7,521	10	80	9,200
	240	80	160	80	4,870	160	80	4,714	10	230	7,521	10	80	9,200
	260	80	180	80	4,870	180	80	4,714	10	250	7,521	10	80	9,200
	280	80	200	80	4,870	200	80	4,714	10	270	7,521	10	80	9,200
	300	80	220	80	4,870	220	80	4,714	10	290	7,521	10	80	9,200
	320	80	240	80	4,870	240	80	4,714	10	310	7,521	10	80	9,200
	340	80	260	80	4,870	260	80	4,714	10	330	7,521	10	80	9,200
	360	80	280	80	4,870	280	80	4,714	10	350	7,521	10	80	9,200
	380	80	300	80	4,870	300	80	4,714	10	370	7,521	10	80	9,200
	400	80	320	80	4,870	320	80	4,714	10	390	7,521	10	80	9,200
	450	80	370	80	4,870	370	80	4,714	10	440	7,521	10	80	9,200

For more information regarding measurement and design, see the SPAX design information at <https://downloads.spax.com>





Flat countersunk head, Partial thread, T-STAR plus

With milled ribs, case hardened, slide-coated



Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length partial thread LgT	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
12.0 Ø dk = 22.6 mm	100	60	50	25	250	7,000	0191011201005	4003530245404
	160	100	50	25	250	6,000	0191011201605	4003530245435
	180	100	50	25	250	6,000	0191011201805	4003530245442
	220	100	50	25	250	6,000	0191011202205	4003530245466
	240	100	50	25	–	2,400	0191011202405	4003530245473
	350	100	50	25	–	1,800	0191011203505	4003530245510
	450	100	50	25	–	1,500	0191011204505	4003530245534
	500	100	50	25	–	1,500	0191011205005	4003530245541
	550**	100	50	20	–	960	0191011205505	4003530245558
	600**	100	50	20	–	960	0191011206005	4003530245565

** alternative design



Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product			Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]			Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length partial thread LgT	t_1 [mm]	t_2 [mm]	$F_{v,Rk}$ [N]	t_1 [mm]	l_{ef} [mm]	$f_{ax,d1,k}$ [N/mm]	t_1 [mm]	t_2 [mm]	$F_{v,Rk}$ [N]	t_1 [mm]	l_{ef} [mm]	$f_{ax,d1,k}$ [N/mm]
12.0 $\varnothing d_k = 22.6$ mm	100	60	40	60	4,736	40	60	4,944	12	88	9,034	12	60	7,920
	160	100	60	100	5,610	60	100	4,944	12	148	10,354	12	100	13,200
	180	100	80	100	6,595	80	100	6,427	12	168	10,354	12	100	13,200
	220	100	120	100	6,595	120	100	6,427	12	208	10,354	12	100	13,200
	240	100	140	100	6,595	140	100	6,427	12	228	10,354	12	100	13,200
	350	100	250	100	6,595	250	100	6,427	12	338	10,354	12	100	13,200
	450	100	350	100	6,595	350	100	6,427	12	438	10,354	12	100	13,200
	500	100	400	100	6,595	400	100	6,427	12	488	10,354	12	100	13,200
	550**	100	450	100	6,595	450	100	6,427	12	538	10,354	12	100	13,200
	600**	100	500	100	6,595	500	100	6,427	12	588	10,354	12	100	13,200

Explanations regarding the load-carrying capacity tables



$F_{v,Rk}$ = Characteristic value for lateral load-carrying capacity per shear joint and connector under lateral load (shearing off), including ΔR_k increase in the characteristic value for load-carrying capacity R_k proportionately by ΔR_k (hanging or rope effect)

$F_{ax,\alpha,Rk}$ = Characteristic value for axial load-carrying capacity per connector (withdrawal)

Wood (C24) = Characteristic density (ρ) $k = 350 \text{ kg/m}^3$

The respective, specified characteristic values for load-carrying capacity must be lowered by safety factor coefficients to the design values for load-carrying capacity. The safety factor coefficients depend on the climatic, environmental conditions (k_{mod}) and the load effect duration class (γ_M).

For more information regarding measurement and design, see the SPAX design information at <https://downloads.spax.com>



Washer head, Partial thread, T-STAR *plus*

4CUT, case hardened, slide-coated

A9J




Dimensions [mm]				Packaging units			SPAX-No.	EAN code	
Thread Ø d1	Length total Ls	Longth thread Lg	Bit Size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty			
6.0 Ø d _k = 13.6 mm	40	37	■	30	200	2,000	64,000	0251010600405	4003530257490
	60	56	■	30	200	2,000	56,000	0251010600605	4003530248351
	80	61	■	30	100	1,000	28,000	0251010600805	4003530245572
	100	61	□	30	100	1,000	32,000	0251010601005	4003530245589
	120	68	□	30	100	1,000	28,000	0251010601205	4003530245596
	140	68	□	30	100	1,000	28,000	0251010601405	4003530245602
	160	65	□	30	100	1,000	28,000	0251010601605	4003530245619
	180	65	□	30	100	1,000	28,000	0251010601805	4003530245626
	200	65	□	30	50	500	12.000	0251010602005	4003530248474
	220	65	□	30	50	–	12.000	0251010602205	4003530250002
	250	65	□	30	50	–	4.800	0251010602505	4003530248511
	280	65	□	30	50	–	4.800	0251010602805	4003530253133
	300	65	□	30	50	–	4.800	0251010603005	4003530248528
8.0 Ø d _k = 20 mm	50*	46	■	40	50	500	16,000	0251720800505	4003530182358
	80	70	■	40	50	500	14,000	0251010800805	4003530165184
	100	80	■	40	50	500	14,000	0251010801005	4003530245640
	120	80	■	40	50	500	14,000	0251010801205	4003530245657
	140	80	□	40	50	500	14,000	0251010801405	4003530245664
	160	80	□	40	50	500	14,000	0251010801605	4003530245671
	180	80	□	40	50	500	14,000	0251010801805	4003530245688
	200	80	□	40	50	500	12,000	0251010802005	4003530245695
	220	80	□	40	50	500	12,000	0251010802205	4003530245701
	240	80	□	40	50	–	4,800	0251010802405	4003530245718
	260	80	□	40	50	–	4,800	0251010802605	4003530245725
	280	80	□	40	50	–	4,800	0251010802805	4003530245732
	300	80	□	40	50	–	4,800	0251010803005	4003530245749
	320	80	□	40	50	–	3,600	0251010803205	4003530245756
	340	80	□	40	50	–	3,600	0251010803405	4003530245763
	360	80	□	40	50	–	3,600	0251010803605	4003530245770
	380	80	□	40	50	–	3,600	0251010803805	4003530245787
	400	80	□	40	50	–	3,600	0251010804005	4003530245794
	450	80	□	40	25	–	1,500	0251010804505	4003530245800
	500	80	□	40	25	–	1,500	0251010805005	4003530257254
550	80	□	40	25	–	1,200	0251010805505	4003530257261	


■ T-STAR *plus*, Full thread

□ T-STAR *plus*, Partial thread

*alternative design: P5J




Shear



Withdrawal


Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product				Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]				Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length thread Lg		t_1 [mm]	t_2 [mm]	$F_{v,Rk}$ [N]	t_1 [mm]	l_{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]	t_1 [mm]	t_2 [mm]	$F_{v,Rk}$ [N]	t_1 [mm]	l_{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]
6.0 $\varnothing d_k = 13.6$ mm	40	37	■							6	34	2,409	4	36	2,592
	60	56	■	24	36	1,867	24	36	2,592	6	54	3,219	4	56	4,032
	80	61	■	32	48	2,131	24	56	2,848	6	74	3,345	4	61	4,392
	100	61	□	40	60	2,301	41	59	3,703	6	94	3,345	4	61	4,392
	120	68	□	50	70	2,515	52	68	3,703	6	114	3,471	4	68	4,896
	140	68	□	70	70	2,515	72	68	3,703	6	134	3,471	4	68	4,896
	160	65	□	90	70	2,515	95	65	3,703	6	154	3,471	4	65	4,680
	180	65	□	110	70	2,515	115	65	3,703	6	174	3,471	4	65	4,680
	200	65	□	130	70	2,515	135	65	3,703	6	194	3,471	4	65	4,680
	220	65	□	150	70	2,515	155	65	3,703	6	214	3,471	4	65	4,680
	250	65	□	180	70	2,515	185	65	3,703	6	244	3,471	4	65	4,680
	280	65	□	210	70	2,515	215	65	3,703	6	274	3,471	4	65	4,680
	300	65	□	230	70	2,515	235	65	3,703	6	294	3,471	4	65	4,680
8.0 $\varnothing d_k = 20$ mm	50*	46	■							6	44	3,042	6	44	4,224
	80	70	■	30	50	3,118	30	50	4,800	10	70	5,293	10	70	6,720
	100	80	■	40	60	3,514	40	60	5,200	10	90	5,533	10	80	7,680
	120	80	■	50	70	3,855	50	70	5,200	10	110	5,533	10	80	7,680
	140	80	□	60	80	4,245	60	80	6,760	10	130	5,533	10	80	7,680
	160	80	□	80	80	4,245	80	80	6,760	10	150	5,533	10	80	7,680
	180	80	□	100	80	4,245	100	80	6,760	10	170	5,533	10	80	7,680
	200	80	□	120	80	4,245	120	80	6,760	10	190	5,533	10	80	7,680
	220	80	□	140	80	4,245	140	80	6,760	10	210	5,533	10	80	7,680
	240	80	□	160	80	4,245	160	80	6,760	10	230	5,533	10	80	7,680
	260	80	□	180	80	4,245	180	80	6,760	10	250	5,533	10	80	7,680
	280	80	□	200	80	4,245	200	80	6,760	10	270	5,533	10	80	7,680
	300	80	□	220	80	4,245	220	80	6,760	10	290	5,533	10	80	7,680
	320	80	□	240	80	4,245	240	80	6,760	10	310	5,533	10	80	7,680
	340	80	□	260	80	4,245	260	80	6,760	10	330	5,533	10	80	7,680
	360	80	□	280	80	4,245	280	80	6,760	10	350	5,533	10	80	7,680
	380	80	□	300	80	4,245	300	80	6,760	10	370	5,533	10	80	7,680
	400	80	□	320	80	4,245	320	80	6,760	10	390	5,533	10	80	7,680
	450	80	□	370	80	4,245	370	80	6,760	10	440	5,533	10	80	7,680
	500	80	□	420	80	4,245	420	80	6,760	10	490	5,533	10	80	7,680
	550	80	□	470	80	4,245	470	80	6,760	10	540	5,533	10	80	7,680



Washer head, Partial thread, T-STAR plus

4CUT, case hardened, slide-coated





A9J



Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length thread Lg	Bit Size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
10.0 Ø d _k = 25 mm	80	70	■	50	500	14,000	0251011000805	4003530245817
	100	80	■	50	500	12,000	0251011001005	4003530245824
	120	80	■	50	500	12,000	0251011001205	4003530245831
	140	80	□	50	500	12,000	0251011001405	4003530245848
	160	80	□	25	250	6,000	0251011001605	4003530165207
	180	80	□	25	250	6,000	0251011001805	4003530245862
	200	80	□	25	250	6,000	0251011002005	4003530245879
	220	80	□	25	250	6,000	0251011002205	4003530165214
	240	80	□	25	–	2,400	0251011002405	4003530245893
	260	80	□	25	–	2,400	0251011002605	4003530245909
	280	80	□	25	–	2,400	0251011002805	4003530245916
	300	80	□	25	–	2,400	0251011003005	4003530245923
	320	80	□	25	–	1,800	0251011003205	4003530245930
	340	80	□	25	–	1,800	0251011003405	4003530245947
	360	80	□	25	–	1,800	0251011003605	4003530245954
	380	80	□	25	–	1,800	0251011003805	4003530245961
	400	80	□	25	–	1,800	0251011004005	4003530245978
	450	80	□	25	–	1,500	0251011004505	4003530245985


■ T-STAR plus, Full thread

□ T-STAR plus, Partial thread



Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product				Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]				Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length thread Lg		t_1 [mm]	t_2 [mm]	$F_{v,Rk}$ [N]	t_1 [mm]	l_{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]	t_1 [mm]	t_2 [mm]	$F_{v,Rk}$ [N]	t_1 [mm]	l_{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]
10.0 $\varnothing d_k = 25 \text{ mm}$	80	70	■	40	40	3,539	30	50	5,750	10	70	6,890	6	70	8,050
	100	80	■	40	60	4,539	40	60	6,900	10	90	7,521	10	80	9,200
	120	80	■	50	70	5,012	50	70	7,188	10	110	7,521	10	80	9,200
	140	80	□	60	80	5,417	60	80	7,188	10	130	7,521	10	80	9,200
	160	80	□	80	80	5,992	80	80	9,200	10	150	7,521	10	80	9,200
	180	80	□	100	80	5,992	100	80	9,200	10	170	7,521	10	80	9,200
	200	80	□	120	80	5,992	120	80	9,200	10	190	7,521	10	80	9,200
	220	80	□	140	80	5,992	140	80	9,200	10	210	7,521	10	80	9,200
	240	80	□	160	80	5,992	160	80	9,200	10	230	7,521	10	80	9,200
	260	80	□	180	80	5,992	180	80	9,200	10	250	7,521	10	80	9,200
	280	80	□	200	80	5,992	200	80	9,200	10	270	7,521	10	80	9,200
	300	80	□	220	80	5,992	220	80	9,200	10	290	7,521	10	80	9,200
	320	80	□	240	80	5,992	240	80	9,200	10	310	7,521	10	80	9,200
	340	80	□	260	80	5,992	260	80	9,200	10	330	7,521	10	80	9,200
	360	80	□	280	80	5,992	280	80	9,200	10	350	7,521	10	80	9,200
	380	80	□	300	80	5,992	300	80	9,200	10	370	7,521	10	80	9,200
	400	80	□	320	80	5,992	320	80	9,200	10	390	7,521	10	80	9,200
	450	80	□	370	80	5,992	370	80	9,200	10	440	7,521	10	80	9,200




Cylindric head, Full thread, T-STAR plus

4CUT, case hardened, slide-coated



A9J

Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length full thread LgV	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
6.0 Ø dk = 8.4 mm	80		30	200	2,000	56,000	1211010600805	4003530246364
	100	Thread	30	100	1,000	32,000	1211010601005	4003530246371
	120	close	30	100	1,000	28,000	1211010601205	4003530246388
	140	to	30	100	1,000	28,000	1211010601405	4003530246395
	160	head	30	100	1,000	28,000	1211010601605	4003530246401
	180		30	100	1,000	28,000	1211010601805	4003530246418
	200		30	100	1,000	24,000	1211010602005	4003530246425




Cylindric head, Full thread, T-STAR plus

With CUT point, case hardened, slide-coated




A9J

Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length full thread LgV	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
8.0 Ø dk = 10 mm	160		40	50	500	14,000	1221010801605	4003530257209
	180		40	50	500	14,000	1221010801805	4003530257216
	200		40	50	500	12,000	1221010802005	4003530246432
	220		40	50	500	12,000	1221010802205	4003530246449
	240		40	50	—	4,800	1221010802405	4003530246456
	260	Thread	40	50	—	4,800	1221010802605	4003530246463
	280	close	40	50	—	4,800	1221010802805	4003530246470
	300	to	40	50	—	4,800	1221010803005	4003530246487
	350	head	40	50	—	3,600	1221010803505	4003530246494
	400		40	50	—	3,600	1221010804005	4003530246500
	450		40	50	—	3,000	1221010804505	4003530246517
	500		40	25	—	1,500	1221010805005	4003530257223
	550		40	25	—	1,200	1221010805505	4003530257230
	600		40	25	—	1,200	1221010806005	4003530257247



Shear




Withdrawal


Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product			Wood-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length full thread LgV	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,d1,k}$ [N/mm]
6.0 $\varnothing d_k = 8.4$ mm	80		40	40	2,309	40	40	72,0
	100	Thread	50	50	2,489	50	50	N/mm
	120	close	60	60	2,669	60	60	
	140	to	70	70	2,849	70	70	Max.
	160	head	80	80	3,029	80	80	$f_{tens,d} =$
	180		90	90	3,178	90	90	8,462 N
	200		100	100	3,178	100	100	

see footnote below



Shear



Withdrawal

Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product			Wood-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length full thread LgV	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,d1,k}$ [N/mm]
8.0 $\varnothing d_k = 10$ mm	160		80	80	4,475	80	80	
	180		90	90	4,715	90	90	
	200		100	100	4,955	100	100	
	220		110	110	5,110	110	110	
	240		120	120	5,110	120	120	96,0
	260	Thread	130	130	5,110	130	130	N/mm
	280	close	140	140	5,110	140	140	
	300	to	150	150	5,110	150	150	Max.
	350	head	175	175	5,110	175	175	$f_{ax,d1,k}$
	400		200	200	5,110	200	200	=13,1kN
	450		225	225	5,110	225	225	
	500		250	250	5,110	250	250	
	550		275	275	5,110	250	250	
	600		300	300	5,110	250	250	

Multiply the value $f_{ax,d1,k}$ with the effective thread length ($l_{ef,k}$) in the respective wood component. Lower as appropriate for angle $\alpha < 90^\circ$.
The design value for thread load-carrying capacity must not exceed the design value for steel load-carrying capacity $f_{tens,d}$.

For more information regarding measurement and design, see the SPAX design information at <https://downloads.spax.com>



SPAX-Iso

The insulation screw for roofs and facades




spax.com
„SPAX-Iso“

SPAX-Iso the insulation screw for roofs and facades

The SPAX-Iso screw is suitable for installing soft materials used in over-rafter insulation. Pressure loads, such as those caused by roofing or snow loads, cannot be absorbed by compressible insulating materials. Partial-thread screws are not suitable for installing compressible insulating materials.


Thanks to SPAX-Iso, installing compressible insulating materials is not a problem. The fixing thread holds the counter-batten tight and transfers the compressive forces. This keeps the insulating material in shape..

 You can also use the SPAX design software to calculate your projects at: <https://designsoftware.spax.com>.



Cylinder head, T-STAR plus

4CUT, fixing thread, case hardened, slide-coated



A9J




Dimensions [mm]				Packaging units		SPAX-No.	EAN code
Thread- Ø d1	Length total Ls	Length partial thread LgT	BIT size T	SPAX BOX [pieces]	Master carton [pieces]		
10.0 Ø dk = 12.3 mm	200	80	50	50	500	0491011002005	4003530252761
	230	80	50	50	500	0491011002305	4003530252778
	260	80	50	50	500	0491011002605	4003530252785
	290	80	50	50	500	0491011002905	4003530252792
	320	80	50	50	500	0491011003205	4003530252808
	350	80	50	50	500	0491011003505	4003530252815

Penetration depth in rafter [mm]

Screw length [mm]	200		230		260		290		320		350	
Batten thickness [mm]	40	60	40	60	40	60	40	60	40	60	40	60
Insulating-material thick- ness [mm]*												
60	91	70	121	100	151	130	181	160	211	190	241	220
80	70	48	100	78	130	108	160	138	190	168	220	198
100	48	-	78	56	108	86	138	116	168	146	198	176
120	-	-	56	-	86	64	116	94	146	124	176	154
140	-	-	-	-	64	43	94	73	124	103	154	133
160	-	-	-	-	43	-	73	51	103	81	133	111
180	-	-	-	-	-	-	51	-	81	59	111	89
200	-	-	-	-	-	-	-	-	59	-	89	68
220	-	-	-	-	-	-	-	-	-	-	68	46

Minimum thread depth in rafter = batten thickness or min. 4xd1 acc. to ETA-16/0617

* If the roof boarding is used, this has to be taken into account when calculating the thickness of the insulating material. E.g. 120 mm insulating material + 20 mm roof boarding = 140 mm in the table



SPAX – Construction

Design guidelines

Guidelines for the design of structural connections with SPAX fasteners

SPAX Design guidelines

These guidelines apply to the design and installation of loadbearing connections with SPAX fasteners in accordance with BS EN 1995-1-1:2004+A2:2014 (Eurocode 5 resp. EC5) and its National Annex dated October 2012, and in accordance with the European Technical Approval ETA-12/0114.

It is aimed at quick predesign of loadbearing connections with SPAX fasteners, but is not intended to replace appropriate engineering and design by a design professional.

In absence of further specific provisions in the European Technical Approval (ETA), EC5 and its National Annexes apply to the design and installation of connections. Outside the European Union, national standards shall be considered as well.

This document solely covers requirements relative to load-carrying capacity and serviceability of connections.

In addition to EC5 provisions, specific design prescriptions are provided in the relevant sections, and shall be considered as minimum requirements. They may need to be extended to particular connection configurations.

Members of solid timber, glued-laminated timber, laminated veneer lumber (LVL), wood-based products (in accordance with their ETA or national approval) or steel may be connected to further members of solid timber, glued-laminated timber, laminated veneer lumber (LVL), wood-based products (in accordance with their ETA or national approval).

Connections to wood-based panels (particle board, fibre board, OSB or plywood) may be designed in accordance with the prescriptions of the ETA or national approval of the relevant panel, provided screwed connection is accepted or covered in its scope.

This guide has been established in good faith and to the best of our knowledge. No liability is therefore engaged or accepted for any obvious mistake or error.

Please send any suggestion, question or proposal for corrections to technik@spax.com.



For more information regarding measurement and design, see the SPAX design information at <https://downloads.spax.com>



SPAX
Design guidelines

Verification of load-carrying capacity

Shear

Design value for lateral load-carrying capacity

$$F_{v,Rd} = \frac{k_{mod} \cdot F_{v,Rk}}{\gamma_M} \quad [N] \quad \gamma_M = 1.3$$

Verification of lateral load-carrying capacity

The following requirement must be met:

$$\frac{F_{v,Ed}}{n_{ef} \cdot F_{v,Rd}} \leq 1 \quad (\text{If } n_{ef} \text{ has already been taken into consideration in } F_{v,Rd}, \text{ then it must not be considered again here.})$$

Withdrawal capacity

Design value for axial load-carrying capacity

To calculate the withdrawal load capacity, the design values of three different instances of failure are compared.

The lowest of these is the significant value.

$$F_{ax,\alpha,Rd} = \min. \begin{cases} \text{Design value } F_{ax,\alpha,Rd,2} \text{ for failure related to withdrawing the thread} \\ \text{Design value } f_{tens,d} \text{ for failure related to tensile strength (steel)} \\ \text{Design value } F_{ax,\alpha,Rd,1} = \max. \{ F_{ax,\alpha,Rd,1} ; F_{ax,\alpha,Rhead,d,1} \} \text{ for failure related to head pull-through capacity} \end{cases}$$

Design value related to withdrawing the thread:

$$F_{ax,\alpha,Rd,2} = \frac{k_{mod} \cdot F_{ax,\alpha,Rk,2}}{\gamma_M} \quad [N] \quad \gamma_M = 1.3$$

Design value for tensile strength (steel):

$$f_{tens,d} = \frac{f_{tens,k}}{\gamma_M} \quad [N] \quad \gamma_M = 1.3$$

Design value for head pull-through capacity

$$F_{ax,\alpha,Rd,1} = \frac{k_{mod} \cdot \max \{ F_{ax,\alpha,Rk,1} ; F_{ax,\alpha,Rhead,k,1} \}}{\gamma_M} \quad [N] \quad \gamma_M = 1.3$$

Verification of axial load-carrying capacity

The following requirement must be met:

$$\frac{F_{ax,\alpha,Ed}}{n_{ef} \cdot F_{ax,\alpha,Rd}} \leq 1 \quad (\text{If } n_{ef} \text{ has already been taken into consideration in } F_{ax,\alpha,Rd}, \text{ then it must not be considered again here.})$$

Verification of combined lateral and axial load-carrying capacity

The following requirement must be met:

$$\left(\frac{F_{v,Ed}}{n_{ef} \cdot F_{v,Rd}} \right)^2 + \left(\frac{F_{ax,\alpha,Ed}}{n_{ef} \cdot F_{ax,\alpha,Rd}} \right)^2 \leq 1 \quad (\text{If } n_{ef} \text{ has already been taken into consideration in } F_{v,Rd} \text{ and in } F_{ax,\alpha,Rd}, \text{ then it must not be considered again here.})$$

ETA 3.9

Modification coefficient k_{mod}

Load effect duration class (LEDC)

Classification of effects acc. to DIN EN 1991-1-1, DIN EN 1991-1-3, DIN EN 1991-1-4, DIN EN 1991-1-7, DIN EN 1991-3 and the associated national appendices in the load effect duration classes (LEDC)

	A	B
1	Effect	LEDC
2	Densities and distributed loads acc. to DIN EN 1991-1-1	Constant
3	Vertical imposed loads acc. to DIN EN 1991-1-1	
4	A Attics, living rooms and common rooms	Average
5	B Office spaces, work spaces, corridors	Average
6	C Rooms, meeting spaces and areas where people could gather (except for those categories specified under A, B, D and E)	Short
7	D Sales rooms	Average
8	E1 Storage facilities, factories and workshops, stands, storage spaces and entrances	Long
9	E2 Spaces where forklifts are operated	Average
10	F Areas with traffic and for parking (light vehicles, total load $\leq 30,000$ N), entrance ramps to these areas	Average Short
11	H Roofs where foot traffic is not permitted except for normal maintenance work and repairs	Short
12	K Helicopter loads	Short
13	T Staircases and landings	Short
14	Z Entrances, balconies and similar structures	Short
15	Horizontal loads acc. to DIN EN 1991-1-1	
16	Horizontal imposed loads consisting of people on railings, guard rails and other structures that serve as barriers	Short
17	Horizontal loads for achieving sufficient longitudinal and transverse rigidity	^a
18	Horizontal loads for helicopter landing pads on roofs, – for horizontal imposed loads, – for rollover protection	Short Very short
19	Wind loads acc. to DIN EN 1991-1-4	Short/Very short ^b
20	Snow and ice loads acc. to DIN EN 1991-1-3	
21	Ground elevation of the building location above sea level $\leq 1,000$ m	Short
22	Ground elevation of the building location above sea level $> 1,000$ m	Average
23	Impact loads acc. to DIN EN 1991-1-7	Very short
24	Horizontal loads based on crane and machine operation acc. to DIN EN 1991-3	Short

NA; Tab. NA.1

Effects due to changes in temperature or moisture are part of load effect duration class “Average”.

NA; 2.3.1.2(2)P

Effects due to uneven settlement are part of load effect duration class “Constant”.

For wood components, ignoring the effect of temperature changes is permitted.

NA; 2.3.1.2(2)P

For effects in a combination of loads with various LEDC, the LEDC with the shortest duration can be used to determine the modification coefficient k_{mod} .

NA; 2.3.1.2(2)P

EC5; 3.1.3 (2)

^a In accordance with the associated loads

^b For wind, the average between Short and Very short can be used for k_{mod}

Modification coefficient k_{mod}

Calculation values for modification coefficient k_{mod}

	A	B	C	D	E	F	G	H
1	Material	Standard	Use class	Load effect duration class				
				Constant effect	Long effect	Average effect	Short effect	Very short effect
2	Solid wood	EN 14081-1	1	0.60	0.70	0.80	0.90	1.10
3			2	0.60	0.70	0.80	0.90	1.10
4			3	0.50	0.55	0.65	0.70	0.90
5	Glued laminated timber	EN 14080	1	0.60	0.70	0.80	0.90	1.10
6			2	0.60	0.70	0.80	0.90	1.10
7			3	0.50	0.55	0.65	0.70	0.90
8	Laminated veneer lumber (LVL)	EN 14374, EN 14279	1	0.60	0.70	0.80	0.90	1.10
9			2	0.60	0.70	0.80	0.90	1.10
10			3	0.50	0.55	0.65	0.70	0.90
11	Plywood	EN 636						
12		Type EN 636-1	1	0.60	0.70	0.80	0.90	1.10
13		Type EN 636-2	2	0.60	0.70	0.80	0.90	1.10
14		Type EN 636-3	3	0.50	0.55	0.65	0.70	0.90
15	OSB	EN 300						
16		OSB/2	1	0.30	0.45	0.65	0.85	1.10
17		OSB/3, OSB/4	1	0.40	0.50	0.70	0.90	1.10
18		OSB/3, OSB/4	2	0.30	0.40	0.55	0.70	0.90
19	Particle board	EN 312						
20		Type P4, Type P5	1	0.30	0.45	0.65	0.85	1.10
21		Type P5	2	0.20	0.30	0.45	0.60	0.80
22		Type P6, Type P7	1	0.40	0.50	0.70	0.90	1.10
23		Type P7	2	0.30	0.40	0.55	0.70	0.90
24	Fibreboard, hard	EN 622-2						
25		HB.LA, HB.HLA1 or 2	1	0.30	0.45	0.65	0.85	1.10
26		HB.HLA1 or 2	2	0.20	0.30	0.45	0.60	0.80
27	Fibreboard, medium-hard	EN 622-3						
28		MBH.LA1 or 2	1	0.20	0.40	0.60	0.80	1.10
		MBH.HLS1 or 2	1	0.20	0.40	0.60	0.80	1.10
29		MBH.HLS1 or 2	2	–	–	–	0.45	0.80
30	Fibreboard, MDF	EN 622-5						
31		MDF.LA, MDF.HLS	1	0.20	0.40	0.60	0.80	1.10
32		MDF.HLS	2	–	–	–	0.45	0.80

EC5; Tab. 3.1

For wood material connections, if the modification coefficients k_{mod} of the two components joined together ($k_{mod,1}$ and $k_{mod,2}$), then the following value can be used for k_{mod} :

$$k_{mod} = \sqrt{k_{mod,1} \cdot k_{mod,2}}$$

EC5; 2.3.2.1(2)

NA; Gl. (NA.114)

Modification coefficient k_{mod}

Calculation values for modification coefficients k_{mod} for wood, wood material and gypsum material

	A	B	C	D	E	F	G	H
1	Material	Standard	Use class	Load effect duration class				
				Constant effect	Long effect	Average effect	Short Effect	Very short effect
2	Laminated timber, cross-laminated timber, solid wood boards		1	0.60	0.70	0.80	0.90	1.10
3			2	0.60	0.70	0.80	0.90	1.10
4	Gypsum board (Types GKB ^a , GKF ^a , GKBI and GKFI), gypsum fibreboard	DIN 18180, DIN EN 15283-2	1	0.20	0.40	0.60	0.80	1.10
5			2	0.15	0.30	0.45	0.60	0.80
6	Cement particle board		1	0.30	0.45	0.65	0.85	1.10
7			2	0.20	0.30	0.45	0.60	0.80
8	^a Only Use class 1:							

NA; Tab. NA.4

Safety factor coefficient γ_M for the strength characteristic on the material side

Safety factor coefficient γ_M for the strength characteristics in constant and temporary measurement situations

	A	B
1	Material	γ_M
2	Solid wood, particle board, hard fibreboard, medium-hard fibreboard, MDF fibreboard, soft fibreboard, laminated veneer lumber, plywood, OSB, glued laminated timber	1.3
3	Laminated timber, cross-laminated timber, solid wood boards, fibre-reinforced gypsum board, gypsum board, cement particle board	1.3
4	Steel in connections	
5	– Dowel-type connections subject to bending loads	1.3
6	– Parts subject to tensile or shearing loads when verifying the yield strength in the net cross section	1.3
7	– Verification of load-carrying capacity for boards with regard to nail plates	1.25

NA; Tab. NA.2 + NA.3

For verification of steel parts, use the safety factor coefficients in DIN EN 1993 or the associated national appendices.

NA; 2.4.1

For exceptional measurement situations, apply safety factor coefficients γ_M to 1.0.



SPAX-threaded rod

A better solution for transverse reinforcement
for large components made of glued
laminated timber



The alternative for transverse reinforcement **SPAX threaded rod**

The SPAX threaded rod is primarily used with large components (e.g. made of glued laminated timber) that require additional transverse reinforcement. The availability of long lengths up to 3,000 mm makes it an ideal product to replace glued-in metric threaded rods. Because they are less vulnerable to the negative influences of moisture and temperature change, the SPAX threaded rod is also suitable for later renovations on the construction site.


For pre-drilling, the following drills having a diameter of 12 to 13 mm are recommendable:

FAMAG, Remscheid: Auger BIT
WOODTEC FANKHAUSER,
CH-Vordemwald: Deep hole drill flushed with pressurised air

The following machines are recommended for screwing-in:

PROTOOL DRP 32-4,
BOSCH GBM 32-4,
FEIN angle screwing machine Mammot SCW 16-6,
MAKITA angle screwing machine DA 4301.

Shortening to desired length possible.






Ideal accessory:

SPAX-screw-sleeve, wrench size SW 11 for threaded rods without head



SPAX screw finder



A2J



SPAX-threaded rod

With hex head and shaft ring, synthetic coating

Dimensions [mm]				Packaging units		SPAX-No.	EAN code
Thread- Ø d1	Length total Ls**	Length full thread LgV	Widths across flats	Shaft ring [piece]	Pallet qty*		
16.0 Ø dk = 26 mm	800		SW 22	25	500	35616000108011	4003530189067
	1,000		SW 22	25	500	35616000101011	4003530189074
	1,200	Thread	SW 22	25	500	35616000102011	4003530189081
	1,400	close	SW 22	25	500	35616000103011	4003530189098
	1,600	to	SW 22	25	500	35616000104011	4003530189104
	1,800	head	SW 22	25	300	35616000105011	4003530189111
	2,000		SW 22	25	300	35616000106011	4003530189128
	2,200		SW 22	25	300	35616000107011	4003530189135

* Dimensions 16 x 1,400 to 16 x 2,000 on special pallets

** Additional lengths on request



A2J

SPAX-threaded rod

Without head, synthetic coating

Dimensions [mm]		Packaging units		SPAX-No.	EAN code
Thread Ø d1	Length total Ls**	Shaft ring [piece]	Pallet qty*		
16.0	3,000	10	100	35616000201011	4003530192821

** Additional lengths on request



SPAX-threaded rod also available in Stainless steel A2

Construction accessories

Accessory for SPAX flat countersunk head and washer head 8 mm

SPAX Screwing aid

Practical screwing aid for rooftop insulation.

For use with SPAX 8 mm allowing precise and pinpoint fastening in the rafter (67° angle).

SPAX-No.	5001120800011
EAN code	4003530168956
Packing unit	1 piece in carton



Accessory for threaded rods without head

SPAX-screw-sleeve

Screw-sleeve for SPAX-threaded rod.

For threaded rods without head. Wrench size SW11.

SPAX-No.	5001900900011
EAN code	4003530192845
Sales unit	1 piece in carton





EDELSTAHL®
**Rost
frei**

INOX
STAINLESS STEEL



Stainless steel

**The wood construction product range
in stainless steel**



Protection from corrosion in outdoor areas.

Stainless steel

Galvanised protective coating is often not sufficient to protect steel screws from corrosion in outdoor areas for the long term. Rust is not only ugly, but it also costs money. In particular if the quality of expensive products or components is reduced and related damage occurs.




Expensive reworking and repairs are required. Rust can be prevented. SPAX stainless steel provides protection against corrosion!

Advantages at a glance:

- High-quality austenitic steel
- Provides protection against corrosion
- Particularly suited for use outdoors, on windows and doors, and in areas with moisture



SPAX screw finder





A4
AISI 316

Flat countersunk head, Full thread, T-STAR plus

MULTI Head, CUT point, slide-coated



Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length full thread LgV	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
10.0 Ø dk = 18.6 mm	160		50	50	500	14,000	1208001001605	4003530182501
	200		50	50	500	12,000	1208001002005	4003530182303
	220		50	50	500	12,000	1208001002205	4003530182310
	240		50	50	–	4,800	1208001002405	4003530178689
	260	Thread	50	50	–	4,800	1208001002605	4003530182327
	280	close	50	50	–	4,800	1208001002805	4003530182334
	300	to	50	50	–	4,800	1208001003005	4003530182341
	350	head	50	50	–	3,600	1208001003505	4003530182228
12.0 Ø dk = 18.6 mm	400		50	50	–	3,600	1208001004005	4003530182235
	400		50	25	–	1,800	1208001204005	4003530182242
	450		50	25	–	1,500	1208001204505	4003530182259
	500		50	25	–	1,500	1208001205005	4003530182266
	550		50	20	–	960	1208001205505	4003530182495





A2
AISI 304

Flat countersunk head, Partial thread, T-STAR plus

MULTI Head, CUT point, slide-coated



Dimensions [mm]				Packaging units			SPAX-No.	EAN code
Thread Ø d1	Length total Ls	Length partial thread LgT	BIT size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty		
8.0 Ø dk = 15.1 mm	80	47	40	50	500	14,000	0197000800805	4003530257292
	100	57	40	50	500	14,000	0197000801005	4003530257308
	120	70	40	50	500	14,000	0197000801205	4003530257315
	140	80	40	50	500	14,000	0197000801405	4003530257322
	160	80	40	50	500	14,000	0197000801605	4003530257339
	180	80	40	50	500	14,000	0197000801805	4003530257346
	200	80	40	50	500	12,000	0197000802005	4003530257353
	220	80	40	50	500	12,000	0197000802205	4003530257360
	240	80	40	50	–	4,800	0197000802405	4003530257377
	260	80	40	50	–	4,800	0197000802605	4003530257384
	280	80	40	50	–	4,800	0197000802805	4003530257391
	300	80	40	50	–	4,800	0197000803005	4003530257407



Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal



Product			Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]			Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length full thread LgV	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,d1,k}$ [N/mm]	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,d1,k}$ [N/mm]
10.0 $\varnothing d_k = 18.6$ mm	160		80	80	5,313	80	80		10	150	8,521	10	150	
	200		100	100	5,888	100	100	115,0	10	190	8,521	10	190	115,0
	220		110	110	6,025	110	110	N/mm	10	210	8,521	10	210	N/mm
	240		120	120	6,025	120	120		10	230	8,521	10	230	
	260	Thread	130	130	6,025	130	130	Max.	10	250	8,521	10	250	Max.
	280	close	140	140	6,025	140	140	f_{tens,d} =	10	270	8,521	10	270	f_{tens,d} =
	300	to	150	150	6,025	150	150	15,385 N	10	290	8,521	10	290	15,385 N
	350	head	175	175	6,025	175	175		10	340	8,521	10	340	
	400		200	200	6,025	200	200		10	390	8,521	10	390	
12.0 $\varnothing d_k = 18.6$ mm	400		200	200	8,140	200	200	132,0	12	388	11,512	12	388	132,0
	450		225	225	8,140	225	225	N/mm	12	438	11,512	12	438	N/mm
	500		250	250	8,140	250	250		12	488	11,512	12	488	
	550		275	275	8,140	275	275	Max.	12	538	11,512	12	538	Max.
								f_{tens,d} =						f_{tens,d} =
								21,538 N						21,538 N

Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product			Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]			Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length partial thread LgT	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l _{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]
8.0 $\varnothing d_k = 15.1$ mm	80	70	30	50	2,402	30	47	2,713	10	70	4,078	10	47	4,512
	100	57	40	60	2,736	40	57	2,713	10	90	4,318	10	57	5,472
	120	70	50	70	2,968	50	70	3,527	10	110	4,630	10	70	6,720
	140	80	60	80	2,968	60	80	3,527	10	130	4,870	10	80	7,680
	160	80	80	80	2,968	80	80	3,527	10	150	4,870	10	80	7,680
	180	80	100	80	2,968	100	80	3,527	10	170	4,870	10	80	7,680
	200	80	120	80	2,968	120	80	3,527	10	190	4,870	10	80	7,680
	220	80	140	80	2,968	140	80	3,527	10	210	4,870	10	80	7,680
	240	80	160	80	2,968	160	80	3,527	10	230	4,870	10	80	7,680
	260	80	180	80	2,968	180	80	3,527	10	260	4,870	10	80	7,680
	280	80	200	80	2,968	200	80	3,527	10	270	4,870	10	80	7,680
	300	80	220	80	2,968	220	80	3,527	10	290	4,870	10	80	7,680

Multiply the value $f_{ax,d1,k}$ with the effective thread length ($l_{ef,ef,k}$) in the respective wood component. Lower as appropriate for angle $\alpha < 90^\circ$.
The design value for thread load-carrying capacity must not exceed the design value for steel load-carrying capacity $f_{tens,d}$.

For more information regarding measurement and design, see the SPAX design information at <https://downloads.spax.com>





Washer head, Partial thread, T-STAR *plus*

4CUT, case hardened, slide-coated

Dimensions [mm]				Packaging units			SPAX-No.	EAN code	
Thread Ø d1	Length total Ls	Length thread Lg	Bit Size T	SPAX BOX [pieces]	Master carton [pieces]	Pallet qty			
6.0 Ø d _k = 13.6 mm	60	56	■	30	100	1,000	32,000	0257000600605	4003530183027
	80	61	■	30	100	1,000	28,000	0257000600805	4003530183034
	100	61	□	30	100	1,000	32,000	0257000601005	4003530183041
	120	68	□	30	100	1,000	28,000	0257000601205	4003530183058
	140	68	□	30	100	1,000	28,000	0257000601405	4003530183065
8.0 Ø d _k = 20 mm	50	46	■	40	50	500	14,000	0257000800505	4003530182815
	60	56	■	40	50	500	14,000	0257000800605	4003530182839
	80	70	■	40	50	500	14,000	0257000800805	4003530176760
	100	80	■	40	50	500	14,000	0257000801005	4003530177880
	120	80	■	40	50	500	14,000	0257000801205	4003530177897
	140	80	□	40	50	500	14,000	0257000801405	4003530177903
	160	80	□	40	50	500	14,000	0257000801605	4003530177910
	180	80	□	40	50	500	14,000	0257000801805	4003530182143
	200	80	□	40	50	500	12,000	0257000802005	4003530182181
	220	80	□	40	50	500	12,000	0257000802205	4003530257414
	240	80	□	40	50	–	4,800	0257000802405	4003530257421
	260	80	□	40	50	–	4,800	0257000802605	4003530257438
	280	80	□	40	50	–	4,800	0257000802805	4003530257445
	300	80	□	40	50	–	4,800	0257000803005	4003530257452

■ T-STAR *plus*, Full Thread

□ T-STAR *plus*, Partial thread



Load-carrying capacity values $F_{v,Rk}$ for shear and $F_{ax,\alpha,Rk}$ for withdrawal

Product				Wood-Wood (C24), $\alpha = 90^\circ$						Sheet steel-Wood (C24), $\alpha = 90^\circ$					
Dimensions [mm]				Shear			Withdrawal			Shear			Withdrawal		
Thread $\varnothing$ d1	Length total Ls	Length thread Lg		t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l' _{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]	t ₁ [mm]	t ₂ [mm]	$F_{v,Rk}$ [N]	t ₁ [mm]	l' _{ef} [mm]	$F_{ax,\alpha,Rk}$ [N]
6.0 $\varnothing d_k = 13.6$ mm	60	56	■	24	36	1,946	24	50	2,592	6	54	2,806	4	56	4,032
	80	61	■	32	48	2,010	24	60	2,848	6	74	2,932	4	61	4,392
	100	61	□	40	60	2,010	41	70	2,848	6	94	2,932	4	61	4,392
	120	68	□	50	70	2,222	52	80	2,848	6	114	3,058	4	68	4,896
	140	68	□	70	70	2,222	72	80	2,848	6	134	3,058	4	68	4,896
8.0 $\varnothing d_k = 20$ mm	50	46	■							4	46	2,260	4	46	4,416
	60	56	■							4	56	2,760	4	56	5,376
	80	70	■	30	50	2,924	30	50	4,800	6	74	4,144	6	70	6,720
	100	80	■	40	60	3,357	40	60	5,200	10	90	4,868	10	80	7,680
	120	80	■	50	70	3,385	50	70	5,200	10	110	4,868	10	80	7,680
	140	80	□	60	80	3,775	60	80	6,760	10	130	4,868	10	80	7,680
	160	80	□	80	80	3,775	80	80	6,760	10	150	4,868	10	80	7,680
	180	80	□	100	80	3,775	100	80	6,760	10	170	4,868	10	80	7,680
	200	80	□	120	80	3,775	120	80	6,760	10	190	4,868	10	80	7,680
	220	80	□	140	80	3,775	140	80	6,760	10	210	4,868	10	80	7,680
	240	80	□	160	80	3,775	160	80	6,760	10	230	4,868	10	80	7,680
	260	80	□	180	80	3,775	180	80	6,760	10	250	4,868	10	80	7,680
	280	80	□	200	80	3,775	200	80	6,760	10	270	4,868	10	80	7,680
	300	80	□	220	80	3,775	220	80	6,760	10	290	4,868	10	80	7,680


$F_{v,Rk}$ = Characteristic value for lateral load-carrying capacity per shear joint and connector under lateral load (shearing off), including ΔR_k increase in the characteristic value for load-carrying capacity R_k proportionately by ΔR_k (hanging or rope effect)

$F_{ax,\alpha,Rk}$ = Characteristic value for axial load-carrying capacity per connector (withdrawal)

Wood (C24) = Characteristic density (ρ) $k = 350 \text{ kg/m}^3$

The respective, specified characteristic values for load-carrying capacity must be lowered by safety factor coefficients to the design values for load-carrying capacity. The safety factor coefficients depend on the climatic, environmental conditions (k_{mod}) and the load effect duration class (γ_M).

For more information regarding measurement and design, see the SPAX design information at <https://downloads.spax.com>



SPAX Design Software

Planning and design
of selected connections and reinforcements

SPAX Design Software



Connections and reinforcements in wood constructions

SPAX Design Software is an online solution that is compatible with the most common browsers such as Microsoft Internet Explorer, Google Chrome, Mozilla Firefox, Apple Safari, etc. The software does not require JAVA! With SPAX Design Software you always have access to the most current version and you don't need to download any applications.


You can save your project files on the SPAX server – similar to a cloud. This means that you can access your projects regardless of your location. Of course, you can also save them on your mobile device.

Several calculations can be organised in one managed project. You can quickly find your calculations with the search function.

Four languages are available in the SPAX Design Software: German, English, French and Spanish



SPAX
Design Software





Download portal

Extensive technical information
is available for download in several languages

The SPAX download portal with additional product information

In the SPAX download portal you will find extensive technical information about our products,
e.g. declarations of performance (DoP), approvals, certificates, SPAX Design Software, etc.

downloads.spax.com



downloads.spax.com

SPAX IS NOT ONLY CALLED "INTERNATIONAL" – IT ACTUALLY IS!

Production is carried out at our site in Ennepetal and we export SPAX products to more than 40 countries across all continents.



SPAX® GOES GREEN!

We endorse climate-neutral printing on paper from responsible sources – for you and for our environment.




Image credits:
S. 12: ©hikasterson, thinkstock, S. 13: ©stefanlister, fotolia, ©KatarzynaBialasiewicz, iStockphoto, S. 34: ©Werner Dieterich/Westend61 / Fotoline, S. 36: ©gordonisaunders, panthermedia, S. 43: ©hans siegers, iStockphoto, S. 47: ©marcus brown, iStockphoto, S. 52: ©Emiljan Sekulovski, iStockphoto, S. 54: ©grapestock, iStockphoto
Product photos are non-binding sample images. The sole basis for purchase is the product description.

5110 · 08/2019 · GB/Export · HUTH

SPAX International GmbH & Co. KG
ALTENLOH, BRINCK & CO - GRUPPE SEIT 1823

Kölner Straße 71–77 · 58256 Ennepetal · Germany
Tel.: +49-23 33-799-1967 · Fax: +49-23 33-799-199
info@spax.com · www.spax.com

You can also find us at:

facebook.com/spax
 instagram.com/spax_international
 youtube.com/user/SPAXinternational

SPAX No. 6019

